

HeartSine® samaritan® PAD 350P/360P AEDs

Semi-Automatic/Fully Automatic
Public Access Defibrillators

Data sheet

Compact, easy-to-use, lifesaving technology for public access

Sudden cardiac arrest strikes millions of people a year worldwide with no warning and no pattern.¹ Immediate treatment is vital. A victim's chance of survival dramatically decreases for every minute without treatment.² This means an Automated External Defibrillator (AED) must be close at hand, easy to use and ready to shock.

The semi-automatic HeartSine samaritan PAD 350P (SAM 350P) and fully automatic HeartSine samaritan PAD 360P (SAM 360P) offer a high level of environmental protection, in an easy-to-operate system in the smallest and lightest package available.

The fully automatic SAM 360P detects motion, such as performing CPR or moving the patient, to reduce the likelihood that the user is touching the patient prior to shock delivery.



Ready to shock



Unique Pediatric-Pak

Ensures the appropriate energy level is delivered for children, between 1 and 8 years of age or up to 25 kg (55 lb).



High level of protection from dust and water

Offers IP56 rating, one of the highest ratings in the industry.



Clinically validated technology³

Proprietary electrode technology and SCOPE biphasic technology, a low energy escalating waveform, that automatically adjusts for differences in patient impedance.



Highly portable

With the lightest weight and most compact footprint among leading AEDs, is easily transported and fit into constrained spaces.

Easy-to-follow visual and verbal guides



User-friendly

Easy-to-understand visual and voice prompts guide the rescuer through the entire resuscitation process, including CPR.



One- or two-button operation

With just an ON/OFF button (and the SHOCK button on the SAM 350P), offers a simple, straightforward operation.



Automatic shock delivery / Motion detection

Fully automatic SAM 360P detects motion, such as performing CPR or moving the patient, to reduce the likelihood that the user is touching the patient prior to shock delivery.



Always ready

After the weekly self-test, the Status Indicator flashes to show that the system has passed the self test and is ready for use.

Simple to own



Two parts, one expiration date

The innovative Pad-Pak, an integrated battery and electrode single-use cartridge with one expiration date, offers one simple maintenance change every four years.




Low cost of ownership

Shelf life of four years means that the Pad-Pak offers savings over other defibrillators that require separate battery and electrode replacements.



8-year warranty

Backed by an 8-year limited warranty.



Specifications

Defibrillator

Waveform: Self-Compensating Output Pulse Envelope (SCOPE) optimised biphasic escalating waveform compensates energy, slope and duration for patient impedance

Patient analysis system

Method: Evaluates patient's ECG, electrode contact integrity and patient impedance to determine if defibrillation is required

Sensitivity/Specificity: Meets IEC/EN 60601-2-4

Impedance range: 20-230 ohms

Energy selection

Pad-Pak

Shock 1: 150J

Shock 2: 150J

Shock 3: 200J

Pediatric-Pak:

Shock 1: 50J

Shock 2: 50J

Shock 3: 50J

Charge time (typical):

150J in < 8 seconds,

200J in < 12 seconds

Environmental

Operating/Standby temperature:

0°C to 50°C (32°F to 122°F)

Transport temperature:

0°C to 50°C (32°F to 122°F)

NOTE: It is recommended that the device should be placed in an ambient temperature of between 0°C to 50°C (32°F to 122°F) for at least 24 hours upon first receipt.

Relative humidity: 5% to 95% non-condensing

Enclosure: IEC/EN 60529 IP56

Altitude: -381 to 4 575 metres (-1,250 to 15,000 feet)

Shock: MIL STD 810F Method 516.5, Procedure 1 (40 G's)

Vibration: MIL STD 810F Method 514.5, Procedure 1
Category 4 Truck Transportation – US Highways

Category 7 Aircraft – Jet 737 & General Aviation

Atmospheric pressure: 572 hPa to 1060hPa (429 mmHg to 795 mmHg)

EMC: IEC/EN 60601-1-2

Radiated emissions: IEC/EN 55011

Electrostatic discharge:

IEC/EN 61000-4-2 (8 kV)

RF immunity:

IEC/EN 61000-4-3 80MHz-2.5 GHz, (10 V/m)

Magnetic field immunity:

IEC/EN 61000-4-8 (3 A/m)

Aircraft: RTCA/DO-160G, Section 21 (Category M)

RTCA/DO-227 (ETSO-C142a)

Falling height: 1 metre (3.3 feet)

Physical characteristics

With Pad-Pak inserted:

Size:

20 cm x 18.4 cm x 4.8 cm
(8.0 in x 7.25 in x 1.9 in)

Weight: 1.1 kg (2.4 lb)

Accessories

Pad-Pak Electrode and Battery Cartridge

Shelf life/Standby life: See the expiration date on the Pad-Pak/Pediatric-Pak (4 years from manufacture date)

Weight: 0.2 kg (0.44 lb)

Size:

10 cm x 13.3 cm x 2.4 cm
(3.93 in x 5.24 in x 0.94 in)

Battery type: Disposable single-use combined battery and defibrillation electrode cartridge (lithium manganese dioxide (LiMnO₂) 18V)

Battery capacity (new):

> 60 shocks at 200J or 6 hours of battery use

Electrodes: Disposable defibrillation pads are supplied as standard with each device

Electrode placement: Anterior - lateral (Adult)

Anterior - posterior or Anterior - lateral (Pediatric)

Electrode active area: 100 cm² (15 in²)

Electrode cable length: 1 metre (3.3 feet)

Aircraft safety test (TSO/ETSO-certified Pad-Pak): RTCA/DO-227 (ETSO-C142a)

Data storage

Memory type: Internal memory

Memory storage: 90 minutes of ECG (full disclosure) and event/incident recording

Review: Custom USB data cable (optional) directly connected to PC with Saver EVO Windows-based data review software

Materials used

Defibrillator housing: ABS, Santoprene

Electrodes: Hydrogel, Silver, Aluminium and Polyester

Warranty

AED: 8-year limited warranty

References

1. Mehra R. Global public health problem of sudden cardiac death. *Journal of Electrocardiology*. 2007;40 (6):S118-S122.
2. Graham R, McCoy M, Schultz A. Strategies to Improve Cardiac Arrest Survival, A Time to Act. Institute of Medicine Report, 2015.
3. Walsh SJ, McClelland A, Owens CG, Allen J, McC Anderson J, Turner C, Adgey J. Efficacy of distinct energy delivery protocols comparing two biphasic defibrillators for cardiac arrest. *Am J Cardiol*. 2004;94:378-380.

All claims valid as of April 2020.

For further information, please contact your Stryker representative or visit our web site at strykeremergencycare.com

Emergency Care Public Access

AED users should be trained in CPR and in the use of the AED.

Although not everyone can be saved, studies show that early defibrillation can dramatically improve survival rates. AEDs are indicated for use on adults and children. AEDs may be used on children weighing less than 25 kg (55 lb) but some models require separate defibrillation electrodes.

The information presented is intended to demonstrate Stryker's product offerings. Refer to operating instructions for complete directions for use indications, contraindications, warnings, cautions, and potential adverse events, before using any of Stryker's products. Products may not be available in all markets because product availability is subject to the regulatory and/or medical practices in individual markets. Please contact your representative if you have questions about the availability of Stryker's products in your area. Specifications subject to change without notice.

Stryker or its affiliated entities own, use, or have applied for the following trademarks or service marks: HeartSine, Pad-Pak, Pediatric-Pak, samaritan, Saver EVO, SCOPE, Stryker. All other trademarks are trademarks of their respective owners or holders. All other trademarks are trademarks of their respective owners or holders.

The absence of a product, feature, or service name, or logo from this list does not constitute a waiver of Stryker's trademark or other intellectual property rights concerning that name or logo.

Made in U.K.

04/2020

H009-032-341-3

Copyright © 2020 HeartSine Technologies. All rights reserved.



CE Class IIb (0123)

HeartSine Technologies Ltd.
203 Airport Road West
Belfast, BT3 9ED
United Kingdom
Tel +44 28 9093 9400
Fax +44 28 9093 9401
heartsinesupport@stryker.com
heartsine.com

Stryker European Operations
B.V. Herikerbergweg 110
1101 CM Amsterdam
Netherlands
Tel +31 (0)43 3620008
Fax +31 (0)43 3632001



UL Classified. See complete marking on product.